

AUTOTROL 363 VALVE

AUTOMATIC FILTER VALVE

COMPACT, LOW-PROFILE SOLUTION FOR A BROAD RANGE OF FILTRATION APPLICATIONS



FEATURES / BENEFITS

Time-tested Duraflow flapper provides frictionless sealing for longer service life

Fiber-reinforced polymer valve body for superior strength and durability, non-corrosive, and UV-resistant

Optical sensor for precision cycle positioning

Fully adjustable 3 cycle control for efficient and reliable water treatment system

Continuous service flow rate of 21 GPM with a backwash of 19 GPM

Backwash capability accommodates filter up to 36" in diameter

Super capacitor for keeping time of day during power outage

Environmental protective cover for water resistance, corrosion resistance, and UV stability

Programming stored in memory and will not be lost due to power outages

History data for valve performance

Designed for single tank systems only

External drain line flow control

OPTIONS

Filter only control valve

Plumbing connections in .75"-1.25" NPT and BSP

Remote regeneration kit

604- Simple economic electronic time clock control.



TESTED and CERTIFIED by the WQA to NSF/ANSI Standard 44 for Water Softener Performance.



UL recognized to the 979



TESTED EMC and Low Voltage Directive



Restriction of Hazardous Substance Compliant

ELECTRICAL

Controller Operating Voltage

Motor Operating Voltage

APPLICATIONS

North American Wall Mount	120/230 VAC
North American Outdoor	120 VAC
Japan Wall Mount	100 VAC
Australian Wall	240 VAC
British Wall	240 VAC
EU Cord Conn	240 VAC
European Wall Mount	240 VAC

ALTERNATE SPECIFICATIONS

Valve Body	Glass-filled Noryl
Valve Color	Black

Operating Pressure

Water Temperature

Ambient Temperature

Cycle Steps

Service Capabilities

PERFORMANCE

Drain Line Flow Control	4-20 gpm
Full Flow Body	Service: 21 gpm Backwash: 19 gpm Fast Rinse: 5 gpm

ALTERNATE CONNECTION

Tank Thread	2.5"
Inlet/Outlet	1" NPT or 1" BSP
Inlet/Outlet (center to center)	4"
Drain Location	0.75" below inlet/outlet

DIMENSIONS

Width	7.8"
Height	3.35"
Riser Tube Dia.	1.05"
Riser Height	Flush +/- 0.5"



LOCATION & OFFICE

5730 NORTH GLEN PARK ROAD, MILWAUKEE, WI 53209
P: 262.238.4400 | F: 262.238.4404 | WWW.PENTAIRAQUA.COM | CUSTOMER CARE: 800.279.9404

All Pentair trademarks and logos are owned by Pentair, Inc. or its affiliates. All other registered and unregistered trademarks and logos are the property of their respective owners. Because we are continuously improving our products and services, Pentair reserves the right to change specifications without prior notice.

Pentair is an equal opportunity employer.

4002833 REV B MR14 © 2014 Pentair Residential Filtration, LLC All Rights Reserved.